

## BEST AVAILABLE COPY

**POLYESTER RESIN PELLET AND ITS PRODUCTION, POLYESTER MOLDED PRODUCT USING THE SAME**

**Patent number:** JP11005892  
**Publication date:** 1999-01-12  
**Inventor:** YUKI KIWAMU; MATSUDA TSUNETOSHI  
**Applicant:** UNITIKA LTD  
**Classification:**  
**- international:** C08L67/02; B29C49/00; B65D1/09; C08G63/88;  
C08J3/12; B29L22/00  
**- european:**  
**Application number:** JP19970160876 19970618  
**Priority number(s):** JP19970160876 19970618

**Abstract of JP11005892**

**PROBLEM TO BE SOLVED:** To obtain the subject pellet capable of reducing the by-production of cyclic oligomers on its melt-molding without inhibiting a solid phase polymerization reaction by covering the surface layer of the specific polyester resin pellet with a specific phosphorus compound.

**SOLUTION:** This polyester resin pellet is obtained by covering (A) a part or all parts of polyethylene terephthalate pellet or a polyester resin pellet consisting mainly of the polyethylene terephthalate preferably produced by the melt-polycondensation of terephthalic acid component and ethylene glycol component as main components and having an intrinsic viscosity of 0.5-1.5 with (B)  $\leq 1$  wt.% of a phosphorus compound containing a phosphorus atom having an oxidation number of V and comprising one kind of phosphoric acid selected from orthophosphoric acid, metaphosphoric acid, polymetaphosphoric acid of the formula:  $(\text{HPO}_3)_m$  [(m) is  $\geq 3$ ] and polyphosphoric acid of the formula:  $\text{H}_{n+2}\text{P}_n\text{O}_{3n+1}$  [(n) is  $\geq 2$ ] or its salt or ester. A method for covering the component A with the component B includes a method comprising spraying the powder of the component B on the component A.

---

Data supplied from the esp@cenet database - Worldwide